



m	steam inlet	
l	water tanks motor	Siemens, 0.55KW
k	water tank manhole	
j	oil tank motor	Siemens, 0.55KW
i	air filter	GMP standard
h	oil tank manhole	
g	Vaccum hole	GMP Standard
f	manhole	
e	material inlet	GMP Standard
d	air filter	GMP Standard
c	Essence cup	
b	LED light	
a	spare	
序号	名称	

12	water tank	design capacity 80L
11	oil tank	design capacity 50L
10	cooling water inlet	
9	emergency stop switch	
8	PLc touch screen	Siemens (chineses&english version)
7	POWER Indicator	
6	hydraulic Pole	
5	top cover	Built-in speed reducer + 1.5KW mixing moto :
4	Homogeneous motor	4.0KW
3	Outside the circular pipe	
2	dischange Pour the button	
1	main tank	100L
序号	名称	

						100L液压升降真空乳化机			志同®机械
标记	处数	分区	更改文件号	签名	年月日	阶段标记	重量	比例	
设计	乙JW		标准化						
校核			批准						
审核									
工艺			日期		0907	共张第张	版本	替代	

Remark :

1. Steam heating Method with temperature sensor for real time monitoring  
Steam Heating SS 316L and Power rating with double jacket design to avoid scaling
2. Mixing type : Clockwise and counterclockwise
3. Button panel control with double side welding and 5 batches polishing
4. Internal and External both Hygiene grades polishing as per GMP Standards
5. Mixing Motor Siemens SS316L
6. Welding Mirror Polish 5 times conforming to GMP Standards
7. Control panel buttons to be in English
8. Middle layer in SS316L and thickness conformity standards (No compromises on thickness)
9. Material Filter, Pressure Meter, Temperature Sensor required type GMP
10. Frame agitator with Teflon blade in SUS316L
11. All material contact with the product should be in SUS 316L
12. Electric cabinet SUS304 with min thickness 2mm , Mirror finish
13. Temperature control , Bottom Inserted Sanitary type PT100 50-200C
14. Ladder thickness and material of construction SUS304
15. Welding procedure as per GMP